

To select the proper load and inflation table, locate your tire size in the following pages, then match your tire's sidewall markings to the table with the same sidewall markings. If your tire's sidewall markings do not match any table listed, please contact your Michelin dealer for the applicable load and inflation table.

Industry load and inflation standards are in a constant state of change, and Michelin continually

product information to reflect these changes. Printed material may not reflect the latest load and inflation standards.

NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.

S = Single configuration, or 2 tires per axle.

245/70R19.5 LRF XRV®

PSI		80	85	90	95	MAXIMUM LOAD AND PRESSURE ON SIDEWALL			
kPa		550	590	620	660				
LBS	SINGLE	7280	7480	7780	8160	S	4080	LBS at	95 PSI
	DUAL	13660	14060	14620	15440	D	3860	LBS at	95 PSI
KG	SINGLE	3300	3400	3540	3700	S	1850	KG at	660 kPa
	DUAL	6200	6360	6640	7000	D	1750	KG at	660 kPa

265/70R19.5 LRH X® LINE™ ENERGY T 19.5

PSI		75	80	85	90	95	100	105	110	115	123	MAXIMUM LOAD AND PRESSURE ON SIDEWALL			
kPa		520	550	590	620	660	690	720	760	790	850				
LBS	SINGLE	8250	8680	9110	9540	9960	10380	10790	11200	11610	12010	S	6005	LBS at	123 PSI
	DUAL	15580	16420	17220	18040	18840	19620	20400	21180	21940	22700	D	5675	LBS at	123 PSI
KG	SINGLE	3740	3920	4140	4320	4540	4700	4860	5080	5240	5450	S	2725	KG at	850 kPa
	DUAL	7080	7400	7840	8160	8560	8880	9200	9600	9920	10300	D	2575	KG at	850 kPa

265/70R19.5 LRG XDE® 2+, XZE® 2+

PSI		65	70	75	80	85	90	95	100	105	110	MAXIMUM LOAD AND PRESSURE ON SIDEWALL			
kPa		450	480	520	550	590	620	660	690	720	760				
LBS	SINGLE	7230	7680	8110	8540	8970	9390	9800	10210	10620	11020	S	5510	LBS at	110 PSI
	DUAL	13660	14500	15320	16140	16940	17740	18520	19300	20060	20820	D	5205	LBS at	110 PSI
KG	SINGLE	3280	3460	3700	3860	4080	4240	4460	4620	4780	5000	S	2500	KG at	760 kPa
	DUAL	6200	6520	6960	7280	7720	8040	8440	8720	9040	9440	D	2360	KG at	760 kPa

285/70R19.5 LRH XDE® 2+, XZE® 2+

PSI		75	80	85	90	95	100	105	110	115	120	MAXIMUM LOAD AND PRESSURE ON SIDEWALL			
kPa		520	550	590	620	660	690	720	760	790	830				
LBS	SINGLE	8780	9250	9710	10160	10610	11050	11490	11930	12360	12790	S	6395	LBS at	120 PSI
	DUAL	16500	17360	18220	19080	19920	20760	21580	22400	23220	24020	D	6005	LBS at	120 PSI
KG	SINGLE	3980	4180	4420	4600	4820	5000	5180	5400	5580	5800	S	2900	KG at	830 kPa
	DUAL	7480	7840	8280	8640	9080	9400	9720	10160	10480	10900	D	2725	KG at	830 kPa

285/70R19.5 LRJ XTE2®

PSI		85	90	95	100	105	110	115	120	125	130	MAXIMUM LOAD AND PRESSURE ON SIDEWALL			
kPa		590	620	660	690	720	760	790	830	860	900				
LBS	SINGLE	10520	11010	11500	11980	12460	12930	13400	13860	14320	14780	S	7390	LBS at	130 PSI
	DUAL	19760	20680	21600	22500	23400	24280	25160	26040	26920	27760	D	6940	LBS at	130 PSI
KG	SINGLE	4770	4990	5220	5430	5650	5860	6080	6290	6500	6700	S	3350	KG at	900 kPa
	DUAL	8960	9380	9800	10210	10610	11010	11410	11810	12210	12600	D	3150	KG at	900 kPa

305/70R19.5 LRJ XZA®

PSI		75	80	85	90	95	100	105	110	115	120	MAXIMUM LOAD AND PRESSURE ON SIDEWALL			
kPa		520	550	590	620	660	690	720	760	790	830				
LBS	SINGLE	9530	10030	10530	11030	11510	12000	12470	12950	13420	13880	S	6940	LBS at	120 PSI
	DUAL	17560	18500	19420	20320	21220	22100	22980	23860	24720	25580	D	6395	LBS at	120 PSI
KG	SINGLE	4340	4540	4800	4980	5240	5440	5620	5880	6060	6300	S	3150	KG at	830 kPa
	DUAL	7960	8360	8840	9200	9640	10000	10360	10800	11160	11600	D	2900	KG at	830 kPa

445/45R19.5 LRM XTA® 2+ ENERGY

PSI		85	90	95	100	105	110	115	120	125	130	MAXIMUM LOAD AND PRESSURE ON SIDEWALL			
kPa		590	620	660	690	720	760	790	830	860	900				
LBS	SINGLE	14120	14780	15440	16080	16720	17360	17980	18600	19220	19840	S	9920	LBS at	130 PSI
	DUAL											D		LBS at	PSI
KG	SINGLE	6420	6680	7020	7280	7520	7860	8100	8440	8680	9000	S	4500	KG at	900 kPa
	DUAL											D		KG at	kPa

WHEEL DIAMETER - 20"