

8S 24V	Detail	Parameter						Unit
Discharge	Maximal Continuous Discharging Current	80	100	120	150	200	250	A
	Peak Discharging Current	260±30	300±30	360±50	450±10	500±100	600±100	A
Internal Resistance	MOSFET	≤10	≤10	≤10	≤10	≤10	≤10	mΩ
Charge	Charging Voltage	30						V
	Charging Current	80	100	120	150	200	250	A
Over charge protection	Over Charge Detection Voltage	3.75±0.05						V
	Over Charge Detection Delay Time	1						S
	Over Charger Release Voltage	3.55±0.05						V
Cell balancing	Cell balancing Detection Voltage	3,5						V
	Cell balancing Release Voltage	3,5						V
	Cell balancing Current	30±5						mA
Over discharge protection	Over Discharge Detection Voltage	2.2±0.1						V
	Over Discharge Detection Delay Time	1						S
	Over Discharger Release Voltage	2.7±0.1						V
Over current protection	Over Current Detection Delay Time	1						ms
Short Protection	Detection Condition	Exterior Short Circuit						
	Detection Delay Time	250						uS
	Release Condition	Disconnect the load						
Temperature Protection	Temperature Protection	Charge<-5 or >50 Discharge>70						℃
Self-consumption	Working current	100						uA
	Sleeping current(over discharge)	20						uA
Working Temperature	Temperature Range	-20~70						℃
Storage Temperature	Temperature Range	-40~80						℃
Size	80A(66*150*17mm) 100A(66*150*25mm) 120A-150A(66*180*26mm) 200A-250A(120*211*32mm)							